



TOUR PIXEL BAR 1010 II

TB-1010QW II



Control

DMX Channel: 4/5/7/40 Channels
 Control Mode: DMX512, Master/Slave, RDM
 Firmware Upgrade: Update via DMX link


Construction

Display: LED display
 Data In/Out: 3-pin waterproof connector
 Power In/Out: Power cord out
 Protection Rating: IP65


Electrical and Physical

Power Voltage: AC 100~240V, 50/60Hz
 Power Consumption: 130W
 Dimensions(mm): 953x104x112mm, 10kg
 Dimensions(in): 37.5"x4.0"x4.4" in, 22.0lbs

Photometrics Diagram



Dimensions(mm)



TB-1010QW II T (Tour Version)



TB-1010QW II (Fixed Installation Version)



Barn door(Optional)

Specifications

Light Source: 10x15W RGBW LED
 Beam Angle: 10°

Features

Efficient LED lens, uniform color mixing, which makes the light effect better; 0~100% smooth dimming, adjustable electronic strobe effect; LEDs can be controlled pixel by pixel, Equal distance design, horizontal stitching can achieve dynamic water effects, vertical stitching can achieve matrix effect; IP65 design is suitable for fixed installation or mobile performance; Moreover, the fixture can be adjusted to 180° backward and forward by double mounting brackets.

Adding the atomized paper, the full angle can reach 60°, it can expand the effective wash range(optional)

Extra installation of the barn door can prevent glare and stray light effectively(optional)