



Specifications

Light Source: 1x300W cool/warm white LED
 Color Temperature: 3200±200K
 5500±200K (optional)

Features

Manual focus(TS-300M)
 Manual linear dimming,
 zoom range: 18°~31°
 4 dimming curves, 2 optional dimming speed
 0~100% smooth dimming
 Low noise under 35dB@1m
 Rotating barn door and hanger

THEATER SPOT 300 TS-300/TS-300M

Control

DMX Channel: 2/3 Channels(TS-300)
 1/2 Channels(TS-300M)
 Control Modes: DMX, Master/Slave, Manual, Art-Net
 Firmware Upgrade: Update via DMX link

Construction

Display: LCD display
 Data In/Out: 5-pin XLR
 Power In/Out: PowerCon in/out
 Protection Rating: IP20


Optical

CRI: WW≥95, CW≥95
 CQS: WW≥94, CW≥93
 TLCI: WW≥95, CW≥95

Electrical and Physical

Power Voltage: AC 100~240V, 50/60Hz
 Power Consumption: 400W
 Dimensions(mm): 473×278×264mm,10Kg
 Dimensions(in): 18.6"x10.9"x10.3" in, 22.0lbs

Photometrics Diagram



18°Lux	CW	6656	1664	799	416
	WW	5496	1374	610	343
Diameter(m)	CW/WW	1.5	3.1	4.6	6.2
31°Lux	CW	2696	674	300	168
	WW	1864	466	207	116
Diameter(m)	CW/WW	2.7	5.4	8.1	10.8

Dimensions(mm)

