



SABER PERFORMANCE II

XP-16R BEAM II



Control

DMX Channel: 15/17 Channels
 Control Modes: DMX, Wireless (optional), RDM
 Firmware Upgrade: Update via DMX link

Pan/Tilt

Pan/Tilt: 540°/270°
 Pan/Tilt Resolution: 16bit


Construction

Display: LCD display
 Date In/Out: 3-pin XLR
 Power In/Out: PowerCon in/out
 Protection Rating: IP20


Electrical and Physical

Power Voltage: AC 100~240V, 50/60Hz
 Power Consumption: 490W
 Dimensions(mm): 435×344×516mm, 22.2kg
 Dimensions(in): 17.1"×13.5"×20.3" in, 48.9lbs

Photometrics Diagram



Dimensions(mm)



Specifications

Light Source: Philips MSD Platinum 16R
 Color Temperature: 8000K
 Beam Angle: 1°

Features

- Motorized focus
- Color wheel: 12 fixed colors plus open with rainbow effect
- Gobo wheel: 1 Rotating gobo wheel with 12 gobos plus open
- Gobos outside diameter: 9.8mm
- Gobos image diameter: 7mm
- 0~100% smooth dimming
- 8 facet prism+16 facet prism, both of them can rotate in both directions and overlay each other
- Independent frost effect
- Various strobe speeds