



Construction

Power Socket: Power cord out
Protection Rating: IP20

Optical

CRI: WW≥95, CW≥95
CQS: WW≥95, CW≥95
TLCI: WW≥95, CW≥95

Electrical and Physical

Power Voltage: AC 85~127V, 50/60Hz,
AC 175~264V, 50/60Hz
Power Consumption: 24W (E-40T)
17W (E-10T)
Dimension(mm): 273x128x100mm,
1.3Kg (E-40T) /1.1Kg (E-10T)
Dimension(in): 10.7"x5.0"x3.9" in,
2.8lbs(E-40T)/2.4lbs (E-10T)

Features

E-40T/ E-10T is a Track Version, uniform light,
sharp image edge, and self-locking focus lens.
The product takes advantage of the heat pipe heat
conduction and housing feature to dissipate heat
without a fan to prolong LED life.


TRACK 40/10 E-40T/E-10T

Specifications


Light Source: 1 x 36W cool/warm white LED (E-40T)
1 x 12W cool/warm white LED (E-10T)
Color Temperature: 3200±150K/5600±150K (optional)
Beam Angle: 19°/26°/36°/50°

Photometric Diagram


E-40T



E-10T




Dimensions(mm)




Standard Couplings

Feeder-L




Feeder-R



T-Connector-R



Straight connector



L-Connector-L



X-Connector



Straight connector MINI



L-Connector-R



End cap




T-Connector-L



Flexible Connector



Three Line ASA Track



Reference Diagram for choice of Connectors

