



THEATER SPOT 100

LP-TS100



Control

DMX Channel: 2 Channels
 Control Mode: DMX, Manual, Art-Net
 Firmware Upgrade: Update via DMX link

Construction

Display: LED display
 Data In/Out: 5-pin XLR
 Power In/Out: PowerCon in
 Protection Rating: IP20


Optical

CRI: Ra≥90

Electrical and Physical


Power Voltage: AC 100~240V, 50/60 Hz
 Power Consumption: 141W
 Dimensions(mm): 429×377×283mm, 15.8Kg
 DimensionsJ(in): 16.8"×14.8"×11.1" in, 34.8lbs

Photometrics Diagram



12°Lux	CW	9897	3350	1640	838
	WW	6112	2192	1120	548
Diameter(m)	CW/WW	0.6	1.2	1.4	2.4
40°Lux	CW	2457	940	388	235
	WW	2120	831	242	208
Diameter(m)	CW/WW	2.2	3.6	4.9	7.2

Dimensions(mm)



Specifications

Light Source: 1 x 100W cool/warm white LED
 Color Temperature: 3200±150K
 5600±250K (optional)

Features

Motorized linear zoom system
 Beam Angle: 12°~40°
 Rotating barn door and hanger
 0~100% smooth dimming
 Fanless cooling design technology, with quiet operation