

FLANDINA 12 IP

BAR 12 IP

FEATURES

- Light Source: 12x15W RGBW LED
- 12 pcs LED pixel control
- Outstanding strobe effect with variable speed
- 0~100% smooth dimming
- Dual mounting bracket design and the adjustable angle reaches 180 degrees in both direction
- Flicker free management



TECHNICAL SPECIFICATIONS

Light Source

- Light Source: 12x15W RGBW LED
- LED life expectancy: 20,000 hours*


Optical System

- Beam angle: 6°/32°(optional)
- Field angle: 11°/60°(optional)
- Asymmetric angle: 10°X45°

Control and Program

- Display: OLED display
- Control Mode: DMX512, RDM
- Control channels: 50/48/12/8/6/5/4
- Upgrade the firmware via DMX link

PHOTOMETRICS DIAGRAM



Electrical and Connectors

- Input voltage range: 100-240V~ 50/60Hz
- Power consumption: 135 W
- Power In/Out: Waterproof Power Connector in/out
- Data in/out: Waterproof 3-pin or 5-pin XLR
- Protection Rating: IP66

Specification


- Fixture Specification: 1,000 x 82 x 108 mm (39.3" x 3.3" x 4.2")
Weight: 7.2 kg (15.9 lbs)
- Carton Specification: 1,070 x 150 x 190 mm (42.1" x 5.9" x 7.5")
Weight: 7.5 kg (17 lbs) (include carton, one-pack per carton)



(*Light source's working life depends on the cycle ratio of its usage pattern and other environmental factors, such as dust, oil, temperature, humidity, etc.)



INSTALLATION DIMENSIONS



EXTERIOR / OUTDOOR

EXTERIOR / OUTDOOR